

**FTM-10** 

**FTM-10** 

FTM-11

## **Technical Data Sheet**

Product name: 58gsm Yellow Gr Product code:		rasin Release Paper (8-12gf)		Report date Versions	2024/6/3 FT/QA01
Material property					
Project		Unit	Parameter values	Executive	standard
Ration		g/m <sup>2</sup>	58±3	ISO536	
Thickness		um	49±3	ISO534	
Wide in width	l	mm	-	Tape measure	
PE grammage	PE grammage		-	GB/	Г451
Coating gram	Coating grammage		1.2±0.2	FTI	<b>M</b> -7
Quick Release	Quick Release force		4-6	FTN	4-10

gf

gf

%

5-7

9-11

> 90

The material is thermoplastic polyester film with release coating on

the surface, with excellent flatness, tensile strength and high transparency, suitable for roll printing, high-speed die-cutting and

high-speed automatic labeling of self-adhesive products.

## Service environment

Г

NT Release force

Aging release force

Residual continuation rate

Material characteristics

Project	<b>Environment description</b>			
Storage environment:	Temperature 25±10°C	Humidity 50±10%		
Application environment:	Temperature 25±10°C	Humidity 0~85%		

## Attention

1. All descriptions, techniques and recommendations for the use of the materials by Fortey are based on test results that we believe to be credible, but do not constitute a guarantee.

Due to the different conditions of use and processing of the product, please test before use to avoid unknown risks.
The technical documents shall be subject to the current terms of Fortey, and Fortey reserves the right of final interpretation.

address:Changhongling Industrial Park, Nanhai District, Foshan City, Guangdong Province Tax: 0757-85225867 Tel: 0757-85225298